

# Zircon

Reliable and durable



*Crafted for Every Taste*

*Crafted For Every Taste*

# Zircon

## – Reliable and durable

The Zircon is the perfect espresso machine for those who need reliability in a essential model.

Hand built by skilled professionals, with only the best quality components, this machine demonstrates CREM's strong attitude towards quality craftsmanship and technology. User friendly features include: illuminated keypad buttons to control the dose of coffee, double pre infusion system, steam pressure gauge, automatic boiler refill and back-flush program for each group.

The electronic switchboard helps control the dosage of coffee through 5 selection buttons, located above each group. These allow you to dispense the right amount of coffee at the push of a button.



Features based on Zircon 2GR TA.

## Versions



**Zircon 3GR**



**Zircon 2GR**



**Zircon Mini 2GR**




**Zircon Mini 1GR**



**TA Option**  
Available for all versions

## Main features



### **Volumetric dosing (5 button keypad)**

Independent group keypads and digital displays: 3 shot settings/doses, hot water, and group flushing.



### **Double Pre infusion**

Combining Crem's pre infusion chamber group heads together with an electronic pre infusion system.



### **Automatic cleaning**

Auto cleaning means the group head and shower always stay clean and ready for the next brew.

## Technical specifications



	Zircon 3GR	Zircon 2GR	Zircon Mini 2GR	Zircon Mini 1GR
<b>Height, width, depth</b>	530, 980, 590 mm 22, 8.7, 10.3"	530, 680, 590 mm 22, 8.7, 10.3"	530, 460, 590 mm 22, 8.7, 10.3"	530, 460, 590 mm 22, 8.7, 10.3"
<b>Weight</b>	65 Kg   25.3 lb	45Kg   25.3 lb	40.5 Kg   25.3 lb	35.5 Kg   25.3 lb
<b>Power ratings</b>	380-415V 2N~ 4350W 50-60Hz	220-240V~ 3350W 50-60Hz	220-240V~ 2800W 50-60Hz	220-240V~ 2800W 50-60Hz
<b>Boiler(s) capacity</b>	17.5 l	11.5 l	6 l	6 l
<b>Operation pressure</b>	0.8 to 1.2 bar	0.8 to 1.2 bar	0.8 to 1.2 bar	0.8 to 1.2 bar
<b>Water connection</b>	3/8" Internal thread	3/8" Internal thread	3/8" Internal thread	3/8" Internal thread
<b>Noise level</b>	<70dB	<70dB	<70dB	<70dB
<b>Heating element</b>	4000W	3050W	2500W	2500W
<b>Steam wands+HW tap</b>	2+1	1+1	1+1	1+1
<b>Pressure gauge</b>	Single 60 mm	Single 60 mm	Single 40 mm	Single 40 mm
<b>Special customization</b>	On request (MOQ)	On request (MOQ)	On request (MOQ)	On request (MOQ)
<b>Single+Double portafilter</b>	1+3	1+2	1+1	1+1

### Standard Features

- Pressure switch control
- Volumetric dosing (5 button keypad)
- Rotary taps
- Built-in rotatory pump
- Soft pre infusion group chamber
- Electronic pre infusion
- Group auto cleaning cycle
- Black knobs

### Supplied Accessories

- 55-cm inlet hose
- x1 Cleaning membrane
- Drain tube (150 cm)

### Options

- Extra steam wand (Except Zircon 3GR)
- TA Version

**NOTE:** Please check your regional price list for available versions/options and part numbers.